

#### CAT. N° 4 120 83



# SINGLE-PHASE METER EMDX<sup>3</sup> DIRECT CONNECTION - MID COMPLIANT - 63 A - RS485 OUTPUT - 2 MODULES

Pack (number of units)	1
Volume (dm³)	0,502
Weight (g)	161,00

#### Product characteristics

#### Single-phase meters

#### **Direct connection**

■ MID compliant :

Maximum current: 63 AOutput type: RS 485Dual tariff: Yes

■ Number of modules : 2

### General characteristics

#### EMDX<sup>3</sup> electrical energy meters - rail mounting

- Measure the electricity consumed by a single-phase or threephase circuit downstream of the electricity distribution metering
- Display electricity consumption in kWh, as well as other values such as current, active energy, reactive energy and power (depending on the catalogue number)
- Conform to standards IEC 61557-12, IEC 62053-21/23, IEC 62052-11 and IEC 62052-31
- $\blacksquare$  MID compliance ensures accuracy of the metering with a view to recharging for the electricity used

#### Documentation

#### Catalogue pages & additional information

- Description page (p.102)
- Technical page (p.107)

#### Installation & technical data

- <u>F02839EN\_01</u>
- <u>IDP000202\_F02839EN\_07</u>
- LE11306BA
- PR\_412083

## Mark Installation instructions & related documents

- LE11305BD
- LE11306BB 01