


# **USB universal charger - 2.4 A**

Cat. No(s): N4285C2 - NT4285C2 - L4285C2



# 1. USE

For recharging portable devices such as phones, smartphones, tablets, MP3 or MP4 players, loudspeakers, watches, game consoles, powerbanks.


#### 2. RANGE

| Designation                     | Cat. No.                             |
|---------------------------------|--------------------------------------|
| Double USB socket - 5 V=- 2.4 A | □ N4285C2<br>■ NT4285C2<br>■ L4285C2 |

### Colours code:

- □White
- Tech
- Anthracite

# 3. OVERALL DIMENSIONS (mm)



| Α  | В  | С  | D  | E  |
|----|----|----|----|----|
| 44 | 44 | 43 | 11 | 47 |

# 4. CONNECTION

Type of terminals: with screws Terminal capacity: 2 x 2.5 mm<sup>2</sup> **Stripping length: 6 mm Screwdriver: flat 3.5 mm** 

# **5. TECHNICAL CHARACTERISTICS**

#### ■ 5.1 Mechanical characteristics

Impact tests: IK 04

Penetration by solid bodies/liquid: IP 40

#### ■ 5.2 Material characteristics

Material: - Base: PC

- Cover plate: PC
- Halogen free
- UV resistant

Self-extinguishing:

- + 850° C / 30 s for insulating parts holding live parts in place.
- + 650° C / 30 s for other parts made of insulating materials.

#### ■ 5.3 Climatic characteristics

Storage temperature: -  $20^{\circ}$  C to +  $70^{\circ}$  C Operating temperature:  $0^{\circ}$  C to +  $45^{\circ}$  C

#### ■ 5.4 Electrical characteristics

All values listed below are measured at an ambient temperature of  $\pm 25^{\circ}$  and after 15 minutes of operation.

| Nominal input voltage                | 100 - 240 V~ |
|--------------------------------------|--------------|
| Nominal input frequency              | 50-60 Hz     |
| Maximum input current                | 300 mA       |
| Maximum power consumption in standby | 0.1 W        |
| Power average efficiency             | 81 %         |
| Nominal output voltage               | 5 V==        |
| Maximum output current               | 2. A         |

Classe de consommation hors charge et niveau moyen d'efficacité: level VI\*

| Safety-standard  | EN60950-1        |
|------------------|------------------|
| Protection class | II - Low voltage |

\*NB: European Regulation No. 278/2009 of 6 April 2009, Directive 2005/32/EC on eco-design requirements for AC/DC power supplies

# ■ 5.5 Average charging time for devices equipped with litium ion polymer batteries:

- 80 % charged < 1 h 15
- 100 % charged < 2 h 00



# USB universal charger - 2.4 A

# **5. TECHNICAL CHARACTERISTICS** (continued)

#### ■ 5.6 Charge time for a smartphone with 2.4 A charger plug:

| Manufacturer brand | Smartphone model | Charge time to 100 % |
|--------------------|------------------|----------------------|
| Samsung            | Galaxy S6        | 1 h 43               |
| Nokia              | Lumia 735        | 2 h 11               |
| Nokia              | Lumia 930        | 2 h 11               |
| Google             | Nexus 6          | 3 h 02               |
| Google             | Nexus 7          | 2 h 58               |

<sup>\*</sup>Data valid as at 1 March 2016.

**Note:** To optimize the charging time of your device, ensure turn it off during the charging phase.

# 6. CLEANING

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichlorethylene.

**Caution**: A preliminary test should be carried out if specific cleaning products are to be used.

#### 7. STANDARDS AND APPROVALS

 $\label{lem:compliance} Compliance with installation and manufacturing standards. Refer to e-catalogue.$ 

Created: 06/12/2012 **bticing**