

# NÓBILE® MODUS**4**®

TV socket F type

AH2152EB AH2152EH AF2152EA AF2152EB




#### Use

TV socket for cabled installation - 1 module.


Range	
Designation	Item
Modus4 - TV socket F type - 1 modWHITE color	AH2152EB
Modus4 - TV socket F type - 1 modHABANO color	AH2152EH
Nòbile - TV socket F type - 1 mod ANTHRACITE color	AF2152EA
Nòbile - TV socket F type - 1 modWHITE color	AF2152EB

## Overall dimensions [mm]



# Connection

Use coaxial cable with characteristic impedance 75  $\!\Omega\!$  . Stripping length



# Performance

Zo	0		B1	FM	VHF	UHF	SATIF	
Ohm		22/0.6	40-68	87.5-108	120-470	470-862	950-2150	
Ω	V/mA	KHz/V	MHz	MHz	MHz	MHz	MHz	
75	500 mA	1.5dB						

## **Technical characteristics**

#### Protection index

(considering a complete installation, including cover plate)

Penetration by solid bodies/liquid: IP20D

## Mechanical characteristics

Impact test: IK 04

### Material characteristics

Key cover: ABS Halogen-free

UV resistant

Self-extinguishing:

650°C/30 s for other parts made of insulating materials

#### **Electrical characteristics**

Characteristic impedance:  $Z_0 = 75\Omega$ 

Frequency range:  $40 \pm 800 \text{ MHz}$ 

Attenuation: 1,5 dB

#### Climatic characteristics

Storage temperature: -  $10^{\circ}$  C to +  $70^{\circ}$  C Use temperature: - $5^{\circ}$  C to +  $35^{\circ}$  C

# Cleaning

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.

Caution: Always test before using special cleaning products.

## Standards and approvals

Compliance with standards: CEI-EN 61169-1 and CEI 61169-2

Refer to e catalogue

